

# *Chris-Craft*


Documents, Manuals, Service Bulletins and  
Screensavers

<http://www.ccmanuals.crosswinds.net>

This Document Was Scanned By Tom King  
For Use By Anyone in the Pursuit and  
Advancement  
Of Antique And Classic Boating

Questions regarding this document  
can Be Emailed to Me  
At:

[ccmanuals@yahoo.com](mailto:ccmanuals@yahoo.com)



*Chris-Craft*

Service **BULLETIN**

Bulletin: E-106 Revision #3

Date: November 1, 1968

Subject: SPARK PLUGS - CHRIS-CRAFT MARINE ENGINES

CHRIS-CRAFT PART NO.	MFG. PART NO.	ENGINE MODEL	SPARK PLUG GAP	REMARKS:
16.62-06256	UJ-6 (Champion)	4 & 6 Cyl Inline	.025	J-8-J may also be used (Gap .030)
16.13-00138	AC-43-S (AC)	225B	.030	
16.62-06256	UJ-6 (Champion)	283	.025	J-12Y or UJ-12Y may be used for extreme low speed running to eliminate fouling. (Never use J-8-J since pre-ignition at high speed is possible.)
16.62-06256	UJ-6 (Champion)	283F 327F	.025	J-10Y may be used for extreme low speed running to eliminate fouling.
*16.62-06256	UJ-6 (Champion)	307Q 327Q	.028	
16.62-00001	BTF-3 (Autolite)	427	.030	F-10 may also be used (.030)
16.62-07022	F-9-Y (Champion)	430	.034	F-10 may be used in very warm climates
16.62-07340	F-10 (Champion)	431	.030	

\*Addition of new Model Engines

CHRIS-CRAFT CORPORATION

SERVICE DEPARTMENT